

# EVOLUTION WINDOW TINT

## TECHNICAL DATA SHEET

	Visible light		Total solar energy				Key parameters				
	Transmitted (VLT)	Reflected	Transmitted	Reflected	Absorbed	Rejected (TSER)	IR Rejection (940-1400nm)	Thickness	Glare Reduction	UV Rejection	IRER (780-2500nm)
CX 1	1%	4%	31%	6%	63%	59%	77%	2 Mil	93%	99%	29%
CX 3	3%	5%	33%	6%	60%	58%	29%	2 Mil	92%	99%	77%
CX 5	5%	6%	34%	7%	59%	55%	75%	2 Mil	91%	99%	29%
CX 15	15%	7%	35%	7%	58%	54%	70%	2 Mil	79%	99%	29%
CX 25	25%	7%	38%	8%	54%	50%	61%	2 Mil	70%	99%	29%
CX 35	35%	7%	43%	8%	49%	45%	60%	2 Mil	61v	99%	29%
CX 50	50%	8%	49%	9%	42%	40%	27%	2 Mil	48%	61%	29%
XP 5	5%	6%	4%	6%	90%	81%	83%	2 Mil	92%	99%	68%
XP 15	15%	6%	5%	7%	88%	79%	82%	2 Mil	82%	99%	68%
XP 35	35%	7%	10%	7%	83%	74%	82%	2 Mil	61%	99%	68%
XP 50	50%	7%	14%	7%	79%	67%	81%	2 Mil	44%	99%	68%
XP 70	75%	9%	30%	7%	63%	49%	79%	2 Mil	25%	99%	68%
XP PRO 5	5%	6%	2%	6%	92%	90%	97%	2 Mil	91%	99%	79%
XP PRO 15	15%	6%	3%	6%	91%	89%	97%	2 Mil	84%	99%	79%
XP PRO 20	20%	7%	3%	7%	90%	87%	97%	2 Mil	72%	99%	79%
XP PRO 35	35%	7%	4%	7%	89%	78%	97%	2 Mil	62%	99%	79%
XP PRO 50	50%	8%	10%	7%	83%	71%	97%	2 Mil	44%	99%	79%
XP PRO 70	75%	9%	27%	8%	65%	53%	89%	2 Mil	21%	99%	70%

Important notice to purchaser: All statements, technical information and recommendations are based on independent test results as shown above. Before using any product in any application, it is recommended that testing for suitability for intended use is carried out.